



USB CONNECTION

PIN#	FUNCTION	COLOR
1	USB PWR (+5V)	RED
2	USB D-	WHITE
3	USB D+	GREEN
4	USB GND	BLACK
SHIELD	SHIELD	

HIROSE CONNECTION

PIN#	FUNCTION	COLOR
1	N/C	
2	N/C	
3	N/C	
4	USB D+	GREEN
5	N/C	
6	USB D-	WHITE
7	USB POWER (+5V)	RED
8	USB GND	BLACK
9	SHIELD	

REF:

GAGE INPUT: CDI LOGIC INDICATOR, 'USB FORMAT'

DATA SEND: HOST COMMANDS:
 R - INDICATOR READ
 C - CLEAR DISPLAY
 H - TOGGLE HOLD

OUTPUT: USB DEVICE, ACCESSED AS A COM PORT
 9600 BAUD, NO PARITY, 8 DATA BITS, 1 OR 2 STOP BITS,
 ASCII TEXT STRING

POWER: POWER FROM USB PORT SUPPLIES POWER TO INDICATOR

ALL PARTS MUST COMPLY WITH LATEST RoHS DIRECTIVE

CHICAGO DIAL INDICATOR CO.						
<i>1372 REDEKER ROAD, DES PLAINES IL. 60016</i>						
TOLERANCES UNLESS OTHERWISE SPECIFIED .XXX ±.005, .XX ±.010, .X ±.015, 1/X ±.015, X'±.1"						
USB - HIROSE SHIELDED DATA CABLE						
DRAWN BY	DATE	CHECKED BY	DATE	EJN NO.	CAD FILE NO.	SCALE
WFA	11/9/17				G03-0099.SLDDRW	
MATERIAL					SIZE	REV.
					C	G13-0055